

JINTONGDA® WINDRUNNER® EARTHSHAKER® LEMON® GuenOn®

JINTONGDA®

金色坦途 顺通到达  
MADE BY JTD



**WEIFANG JINTONGDA  
TYRE CO.,LTD.**

Your Non-highway Solution

- ◆ OEM
- ◆ WHEEL ASSEMBLING



**WEIFANG JINTONGDA TYRE CO.,LTD.**

Factory Add: Hongguang Street,Xianjia Industrial Park,Gaomi,Shandong,China

Tel: 86-536-2861115 Fax: 86-536-2591115 P.C: 261528

Office Add: RM304,NO.1 Building 7080 Center Square,Kunshan Road,Qingdao,China

Tel: 86-532-66006192 Fax:86-532-85766193 P.C: 266000

E-mail: [jtd@jtdtyre.com](mailto:jtd@jtdtyre.com) [www.jtdtyre.com](http://www.jtdtyre.com)





## COMPANY INTRODUCTION

Weifang Jintongda Tyre Co.,Ltd was established in 1997,located in Gaomi city,is one of the leading manufacturers of tire.

Our factory covers an area of 80,000sqm,have more than 300 employees. With full range of OTR tire,Industrial tire,Agriculture tire and special size tire. Our products exported to Europe,Latin America,Australia,Middle East,Southeast Asia,Africa etc, enjoy high reputation.

We confirmly takes "quality and sincerity" as soul,Adheres to market-oriented, Based on excellent service,Goal as customer demands,Aim to supply safe and practical products.

Welcome and sincerely hope to build good and long-term cooperation with more and more domestic and foreign friends.

**WELCOME TO INVEST MOULDS**  
**WELCOME TO DEVELOP NEW PRODUCTS**  
**WELCOME TO DO OEM**  
**LOOKING FOR AGENT, JOIN US!**

## DIRECTORY

- 1 RADIAL AGRICULTURAL TIRE  
 SKIDSTEER TIRE  
 BACKHOE TIRE  
 EXCAVATOR TIRE  
 ROAD ROLLER TIRE  
 FORKLIFT TIRE  
 SOLID TIRE  
 OTR

- 2 AGRICULTURE TIRE  
 PADDY TIRE  
 IRRIGATION TIRE  
 IMPLEMENT TIRE  
 FLOTATION TIRE  
 TRAILER TIRE  
 TRUCK TIRE



CCC



DOT



REACH



ISO-9001

一流的产品, 永久的服务, 创造价值, 回报社会

FIRST-CLASS PRODUCTS, PERMANENT SERVICE, CREATE VALUE, RETURN SOCIETY

## JT-R1W



SIZE	TYPE	PATTERN	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
320/85R28 (12.4R28)	TL	R-1W	1258	321	11.00	1600	160
340/85R28 (13.6R28)	TL	R-1W	1308	353	12.00	1750	160
380/85R28 (14.9R28)	TL	R-1W	1378	389	13.00	2060	160
420/85R28 (16.9R28)	TL	R-1W	1438	452	15.00	2430	160
380/85R30 (14.9R30)	TL	R-1W	1407	388	13.00	2180	160
420/85R30 (16.9R30)	TL	R-1W	1483	458	15.00	2500	160
460/85R30 (18.4R30)	TL	R-1W	1527	488	16.00	2900	160
420/85R34 (16.9R34)	TL	R-1W	1594	439	15.00	2650	160
460/85R34 (18.4R34)	TL	R-1W	1649	491	16.00	3075	160
420/85R38 (16.9R38)	TL	R-1W	1687	448	15.00	2800	160
460/85R38 (18.4R38)	TL	R-1W	1737	482	16.00	3250	160
520/85R38 (20.8R38)	TL	R-1W	1853	546	18.00	3875	160
460/85R42 (18.4R42)	TL	R-1W	1855	493	16.00	3350	160
520/85R42 (20.8R42)	TL	R-1W	1959	560	18.00	4125	160
520/85R46 (20.8R46)	TL	R-1W	2062	560	18.00	4250	160
420/90R30 (16.9R30)	TL	R-1W	1496	434	13.00	2650	160

## JT-SK 201



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10-16.5	8PR	TL	773	264	8.25	1880	410
10-16.5	10PR	TL	773	264	8.25	2135	520
12-16.5	10PR	TL	831	307	9.75	2540	450
12-16.5	12PR	TL	831	307	9.75	2865	550
14-17.5	14PR	TL	921	349	10.5	3875	550
15-19.5	14PR	TL	1019	389	11.75	4565	480
23x8.5-12	6PR	TL	596	213	7.00	820	340
27x8.5-15	8PR	TL	688	213	7.00	1110	410
27x10.5-15	8PR	TL	688	267	8.50	1180	410

## JT-SK 203



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10-16.5	12PR	TL	773	264	8.25	2135	520
12-16.5	14PR	TL	831	307	9.75	2885	550

## JT-SK 204



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10-16.5	12PR	TL	773	264	8.25	2135	520
12-16.5	14PR	TL	831	307	9.75	2885	550



一流的产品, 永久的服务, 创造价值, 回报社会

FIRST-CLASS PRODUCTS, PERMANENT SERVICE, CREATE VALUE, RETURN SOCIETY



## JT-SK 205

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10-16.5	12PR	TL	773	264	8.25	2135	520
12-16.5	14PR	TL	831	307	9.75	2885	550



## JT-SK 206

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10-16.5	12PR	TL	773	264	8.25	2135	520
12-16.5	14PR	TL	831	307	9.75	2885	550



## JT-SK 207

SIZE	ALIAS	OVERALL DIAMETER mm	SECTION WIDTH mm	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10-16.5	31X6X10	787	251	3415	103
12-16.5	33X6X11	838	278	4075	125
14-17.5	38X7X11	914	278	5650	178
15-19.5	40X9X13	1016	330	7545	275
16/70-20	38X7X13	960	330	6320	208

## JT-I3



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10.5/80-18	10PR	TL	907	274	9.00	1950	370
10.5/80-18	12PR	TL	907	274	9.00	2150	430
12.5/80-18	12PR	TL	985	310	9.00	2625	370
12.5/80-18	14PR	TL	985	310	9.00	2910	430

## JT-F3



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
11L-15	10PR	TL	815	280	8LB	1060	360
11L-15	12PR	TL	815	280	8LB	1175	440
11L-16	10PR	TL	840	280	8LB	1120	360
11L-16	12PR	TL	840	280	8LB	1250	440

## JT-R4



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
14.9-24	12PR	TL	1241	378	W13	2300	200
16.9-24	12PR	TL	1309	429	W15L	2380	200
16.9-28	12PR	TL	1410	429	W15L	3250	260
18.4-26	12PR	TL	1426	467	W16L	4000	250
18.4-28	12PR	TL	1477	467	W16L	4100	250
17.5L-24	10PR	TL	1241	445	W15L	2800	220
19.5L-24	12PR	TL	1314	495	DW16L	3450	230
21L-24	14PR	TL	1378	533	DW18L	4200	250

一流的产品, 永久的服务, 创造价值, 回报社会



## JT-IND 208A

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
19.5L-24	10PR	TL	1314	495	DW16L	3150	210
19.5L-24	12PR	TL	1314	495	DW16L	3450	230



## JT-IND 208B

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
19.5L-24	10PR	TL	1314	495	DW16L	3150	210
19.5L-24	12PR	TL	1314	495	DW16L	3450	230



FIRST-CLASS PRODUCTS, PERMANENT SERVICE, CREATE VALUE, RETURN SOCIETY

## EXCAVATOR TIRE

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
8.25-20	14PR	TT	992	245	6.50	2400	675
9.00-20	14PR	TT	1030	260	7.00	5195	760
10.00-20	16PR	TT	1062	280	7.50	6085	790



## JT-R3

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
23.1-26	12PR	TL	1500	595	DW20	5150	200
23.1-26	16PR	TL	1500	595	DW20	6150	260



## JT-LS 302

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
9.00-20	16PR	TT	1018	259	7.00	4700	725
10.00-20	16PR	TT	1055	278	7.50	5300	800
11.00-20	18PR	TT	1085	293	8.00	6000	825
12.00-20	20PR	TT	1125	315	8.50	6750	900



一流的产品, 永久的服务, 创造价值, 回报社会

FIRST-CLASS PRODUCTS, PERMANENT SERVICE, CREATE VALUE, RETURN SOCIETY



**JT-101**



**JT-103**

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
400-8	8PR	TT	422	108	2.50	690	960
18X7-8	14PR	TT	465	168	4.33	1450	900
5.00-8	10PR	TT	469	131	3.00	1090	1000
6.00-9	10PR	TT	540	160	4.00	1515	860
6.00-15	12PR	TT	705	170	4.50E	2185	830
6.50-10	10PR	TT	590	178	5.00	1725	790
7.00-9	10PR	TT	590	190	5.00	1865	850
7.00-12	12PR	TT	676	192	5.00	2445	860
7.00-15 (29XB-15)	12PR	TT	760	199	5.50	2870	860
7.50-15	12PR	TT	798	215	6.00	3140	790
8.15-15 (28X9-15)	14PR	TT	684	221	7.00	3075	970
8.25-12	12PR	TT	765	235	6.50	3060	720
8.25-15	12PR	TT	834	236	6.50	3545	720
300-15	20PR	TT	840	300	8.00	5940	930
9.00-20	14PR	TT	1038	259	7.00	5195	760
10.00-20	16PR	TT	1073	278	7.50	6085	790
12.00-20	18PR	TT	1146	315	8.50	8360	900



**JT-SL301 JT-SL303 JT-SL304 JT-SL305 JT-SL306**

SIZE	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	RIM	LOAD CAPACITY/ KG BALANCE FORKLIFT				OTHER FORKLIFT 16KM/H
					10KM/H		16KM/H		
					DRIVE	STEER	DRIVE	STEER	
4.00-8	SOLID	423	115	3.00 / 3.75	1055	845	1020	765	730
15X4 1/2-8	SOLID	380	106	3.25 / 3.00	905	725	675	655	625
5.00-8	SOLID	469	126	3.00	1210	970	1175	880	840
16X6-8	SOLID	418	156	4.33	1500	1200	1445	1085	1035
18X7-8	SOLID	457	165	4.33	2350	1880	2265	1700	1620
21X8-9	SOLID	535	189	6.00	2810	2250	2715	2035	1940
23X9-10	SOLID	595	230	6.50	4005	3205	3845	2865	2765
23X10-12	SOLID	595	237	8.00	3980	3420	3820	3210	2980
27X10-12	SOLID	683	235	8.00	4465	3570	4315	3235	3080
6.00-9	SOLID	545	140	4.00	1920	1535	1855	1390	1325
6.50-10	SOLID	597	157	5.00	2840	2110	2545	1910	1820
200/50-10	SOLID	458	198	6.50	2370	1900	2290	1720	1630
6.50-16	SOLID	743	179	5.50	3545	2725	3235	2490	2350
7.00-9	SOLID	578	170	5.00	2370	2015	2805	1925	1785
7.00-12	SOLID	683	168	5.00	3015	2410	2910	2185	2075
7.00-15	SOLID	759	178	5.50 / 6.00	3590	2870	3465	2600	2475
7.50-15	SOLID	774	215	5.50 / 6.00 / 6.50	3690	2950	3425	2570	2450
7.50-16	SOLID	819	181	5.50 / 6.00	3910	3130	3780	2835	2700
7.50-20	SOLID	935	218	6.50	5165	4130	4965	3740	3560
8.15-15	SOLID	706	207	7.00	4090	3270	3945	2960	2820
8.25-12	SOLID	735	206	6.50	3325	2660	3215	2410	2295
8.25-15	SOLID	847	205	6.50	4940	3950	4765	3575	3045
8.25-20	SOLID	902	218	6.50	5425	4340	5420	3930	3475
250-15	SOLID	735	226	7.00 / 7.50	4366	3400	4220	3160	3010
300-15	SOLID	838	258	8.00	5990	4700	5780	4335	4130
9.00-16	SOLID	884	218	6.50	5135	4110	4965	3725	3550
9.00-20	SOLID	1038	238	6.50 / 7.00	6450	5160	6235	4675	4450
10.00-20	SOLID	1073	240	7.50 / 8.00	7240	5795	6995	5240	4995
11.00-20	SOLID	1075	252	8.00	7560	6050	7300	5490	5210
12.00-20	SOLID	1146	290	8.00 / 8.50	8800	7000	8500	6925	6595



一流的产品, 永久的服务, 创造价值, 回报社会

FIRST-CLASS PRODUCTS, PERMANENT SERVICE, CREATE VALUE, RETURN SOCIETY



## JT-G2

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
1300-24	12PR	TT/TL	1278	333	9.00DC	2725	300
1400-24	12PR	TT/TL	1348	362	9.00DC	3075	250
1400-24	16PR	TT/TL	1348	362	9.00DC	3650	350
1600-24	16PR	TT/TL	1459	427	10.00	4500	325



## JT-L2

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
15.5-25	12PR	TT/TL	1278	394	12.00	5600	400
17.5-25	16PR	TT/TL	1375	455	14.00	7300	475
20.5-25	16PR	TT/TL	1498	535	17.00	8250	350
23.5-25	16PR	TT/TL	1617	597	19.50	9500	300



## JT-E3 NEW

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
20.5/70-16	14PR	TT	915	353	10.00	1600	390
16/70-20	18PR	TT	1075	410	13.00	3350	450
17.5-25	16PR	TT/TL	1350	445	14.00	4250	300
20.5-25	20PR	TT/TL	1490	520	17.00	6000	325
23.5-25	20PR	TT/TL	1615	595	19.00	7300	300
26.5-25	28PR	TT/TL	1798	675	22.00	9250	300

## JT-E3/L3



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
13.00-24	12PR	TT/TL	1301	351	10.00	3000	300
14.00-24	20PR	TT/TL	1346	362	10.00	4625	475
14.00-24	24PR	TT/TL	1346	362	10.00	5150	575
14.00-25	20PR	TT/TL	1370	375	10.00	4625	475
14.00-25	24PR	TT/TL	1370	375	10.00	5150	575
15.5-25	12PR	TT/TL	1278	394	12.00	5600	400
16.00-24	20PR	TT/TL	1459	430	11.25	5450	400
16.00-24	24PR	TT/TL	1459	430	11.25	6000	475
16.00-25	28PR	TT/TL	1490	430	11.25	6700	575
16.00-25	32PR	TT/TL	1490	430	11.25	7300	650
16/70-20	14PR	TT/TL	1070	410	13.00	2920	350
16/70-24	14PR	TT/TL	1070	410	13.00	2920	350
14/90-16	16PR	TT/TL	896	215	8.5H	1245	290
17.5-25	16PR	TT/TL	1349	445	14.00	4250	300
17.5-25	20PR	TT/TL	1349	445	14.00	5000	400
20.5-25	16PR	TT/TL	1491	513	17.00	5450	275
20.5-25	20PR	TT/TL	1491	513	17.00	6000	325
23.5-25	16PR	TT/TL	1616	594	19.50	6150	225
23.5-25	20PR	TT/TL	1616	594	19.50	7300	300
26.5-25	24PR	TT/TL	1750	676	22.00	9250	300
26.5-25	28PR	TT/TL	1750	676	22.00	10000	350
18.00-25	28PR	TT/TL	1618	498	13.00	8000	500
18.00-25	32PR	TT/TL	1618	498	13.00	8750	575
18.00-25	40PR	TT/TL	1618	498	13.00	9750	700
29.5-25	28PR	TT/TL	1873	750	25.00	11500	325
29.5-29	28PR	TT/TL	1975	750	25.00	12150	325
29.5-29	32PR	TT/TL	1975	750	25.00	14000	400
1800-33	32PR	TT/TL	1818	498	13.00	10000	575
1800-33	36PR	TT/TL	1818	498	13.00	10600	625

一流的产品, 永久的服务, 创造价值, 回报社会

FIRST-CLASS PRODUCTS, PERMANENT SERVICE, CREATE VALUE, RETURN SOCIETY



JT-E4

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
18.00-25	36PR	TL	1615	495	13.00/2.5	16000	850
18.00-33	36PR	TL	1876	495	13.00/2.5	18500	850
21.00-35	36PR	TL	2052	575	15.00/3.0	23000	750
24.00-35	42PR	TL	2177	650	17.00/3.5	29000	750
24.00-35	48PR	TL	2177	650	17.00/3.5	31500	850
27.00-49	48PR	TL	2703	735	19.50/4.0	43700	775
30.00-51	52PR	TL	2908	820	22.00/4.5	53000	750
33.00-51	50PR	TL	3056	895	24.00/5.0	56000	650
33.00-51	58PR	TL	3056	895	24.00/5.0	61500	750
36.00-51	58PR	TL	3234	990	26.00/5.0	71000	675
40.00-57	68PR	TL	3594	1095	29.00/6.0	92500	725



JT-L5

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
17.5-25	24PR	TT/TL	445	1350	14.00/1.5	9250	700
20.5-25	24PR	TT/TL	520	1490	17.00/2.0	10300	525
23.5-25	28PR	TT/TL	595	1615	19.50/2.5	13600	550
26.5-25	32PR	TL	675	1750	22.00/3.0	17000	550
29.5-25	34PR	TL	750	1875	25.00/3.5	20000	525
29.5-29	34PR	TL	750	1975	25.00/3.5	21200	525
35/65-33	36PR	TL	890	2030	28.00/3.5	23600	525
45/65-45	46PR	TL	1015	2350	36.00/4.5	43750	525



JT-R1

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
4.00-7	4PR	TT	390	112	3.000	250	250
4.00-8	4PR	TT	435	112	3.000	280	250
4.00-10	6PR	TT	475	112	3.000	210	250
4.00-12	4PR	TT	535	112	3.00D	205	240
5.00-10	6PR	TT	500	145	3.00D	240	360
5.00-12	8PR	TT	590	145	4.00E	280	200
5.00-14	8PR	TT	570	145	4.00E	440	250
5.00-15	8PR	TT	680	145	4.00E	485	250
5.50-17	8PR	TT	735	150	4.00E	400	280
6.00-12	8PR	TT	640	165	4.50E	405	250
6.00-14	8PR	TT	690	165	4.50E	450	250
6.00-16	8PR	TT	745	165	4.50E/5.00F	495	250
6.50-14	8PR	TT	705	170	4.50J	660	320
6.50-16	8PR	TT	760	170	4.50E	630	340
6.50-20	8PR	TT	860	170	5.00F	725	310
7.50-16	8PR	TT	810	205	5.50F/5.00F	850	210
7.50-18	8PR	TT	860	205	5.50F	945	370
7.50-20	8PR	TT	910	205	5.50F	1020	370
8-16	12PR	TT	630	170	W6	1250	240
8.3-20	8PR	TT	950	210	W7	880	250
8.3-22	8PR	TT	970	210	W7	810	240
8.3-24	8PR	TT	995	210	W7	810	240
8.5-20	8PR	TT	895	210	W7	780	250
9.00-16	8PR	TT	845	234	6.50H	1090	310
9.5-20	8PR	TT	950	240	W8	955	280
9.5-22	8PR	TT	970	210	W7	810	240
9.5-24	8PR	TT	1050	240	W8	1110	280
11-32	8PR	TT	1360	305	W10	1000	140
11-38	8PR	TT	1540	305	W10	1545	160
11.2-24	8PR	TT	1105	285	W10/W9	1045	180
11.2-28	10PR	TT	1205	285	W10	1305	240
11.2-38	10PR	TT	1459	285	10.00	1055	120
12-38	10PR	TT	1563	298	11	1570	140
12.4-24	8PR	TT	1160	315	W11	1415	230
12.4-28	8PR	TT	1205	315	W10/W9	1115	180
12.4-36	8PR	TT	1465	315	W11	1750	280
13.6-24	10PR	TT	1210	345	W12	1790	250
13.6-28	10PR	TT	1310	345	W12	1910	250
13.6-38	10PR	TT	1565	345	W12	2215	250
14.9-24	10PR	TT	1265	378	W13	1990	230
14.9-26	10PR	TT	1315	378	W13	2055	230
14.9-28	10PR	TT	1365	378	W13	2120	230
14.9-30	10PR	TT	1415	378	W13	2190	230
15-24	10PR	TT	1310	400	W14	2800	280
15.5-38	10PR	TT	1570	395	W14L	2320	230
16.9-24	10PR	TT	1335	429	W15L	1960	200
16.9-28	12PR	TT	1435	430	W15L	2575	240
16.9-30	12PR	TT	1485	430	W15L	2245	170
16.9-34	12PR	TT	1585	430	W15L	2605	200
18.4-26	10PR	TT	1450	467	DW16	2645	180
18.4-30	12PR	TT	1550	465	DW16A	2815	180
18.4-34	12PR	TT	1650	465	W16L	2990	180
18.4-38	12PR	TT	1755	467	W16L	3165	180
18.4-42	12PR	TT	1857	467	W16	3330	180
20.8-38	12PR	TT	1835	528	W18L	3475	160
23.1-26	12PR	TT	1605	587	DW20	3250	170
23.1-30	12PR	TT	1707	587	DW20	3450	170
24.5-32	12PR	TT	1803	622	DW21	4000	170





## JT-R1S

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
12.4-24	8PR	TT	1160	315	W11	1415	230
14.9-24	10PR	TT	1265	378	W13	1990	230
14.9-26	10PR	TT	1315	378	W13	2055	230
14.9-28	10PR	TT	1365	378	W13	2120	230
16.9-28	10PR	TT	1435	430	W15L	2380	200
12.4-36	8PR	TT	1465	315	W11	1750	280
12-38	10PR	TT	1563	304	W11	1570	140
18.4-38	12PR	TT	1755	467	W16L	3575	230
20.8-38	12PR	TT	1835	528	W18L	4000	200
24.5-32	12PR	TT	1803	622	DW21A	4000	170



## JT-R2

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
650-16	6PR	TT	830	165	5.00F	565	250
750-16	8PR	TT	890	195	5.50F	750	300
7-14	8PR	TT	678	178	5.00	685	420
8.3-22	8PR	TT	907	230	W7	880	250
8.3-24	8PR	TT	1050	210	W7	1135	270
9.5-24	8PR	TT	1150	240	W8	1315	240
11.2-24	8PR	TT	1205	285	W10	1465	210
12.4-24	8PR	TT	1080	294	W11	1450	180
12.4-28	8PR	TT	1210	320	W10/W9	1650	140
14.9-24	8PR	TT	1265	378	W13	1760	180
14.9-26	8PR	TT	1415	378	W13	1940	180
18.4-30	10PR	TT	1550	467	W16L	2815	230
18.4-34	10PR	TT	1655	467	W16L	2970	230
18.4-38	10PR	TT	1784	467	W16L	3165	230
19.5L-24	10PR	TT	1345	495	W17	2695	200
23.1-26	12PR	TT	1662	587	DW20	3250	170
23.1-30	12PR	TT	1764	587	DW20	3450	170

## JT-R2A



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
7-14	8PR	TT	678	178	5.00	685	420
8.3-22	8PR	TT	907	230	W7	880	250
8.3-24	8PR	TT	1050	210	W7	1135	270
9.5-16	8PR	TT	960	220	W8	780	230
9.5-22	8PR	TT	970	210	W7	810	240
9.5-24	8PR	TT	1150	240	W8	1315	240
11.2-24	8PR	TT	1205	285	W10	1465	210
12.4-24	8PR	TT	1080	294	W11	1450	180
12.4-28	8PR	TT	1210	320	W10/W9	1650	140

## JT-11



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
7.6L-15	8PR	TT/TL	734	193	5.50	950	360
9.5L-14	8PR	TT/TL	735	240	7.00	1085	300
9.5L-15	8PR	TT/TL	750	240	7.00	1115	300
11L-14	8PR	TT/TL	745	275	8.00	1100	250
11L-15	10PR	TT/TL	775	275	8.00	1145	250
11L-16	10PR	TT/TL	795	275	8.00	1215	250
12.5L-15	12PR	TT/TL	823	315	10.00	1145	250
6.50-16	10PR	TT/TL	735	173	4.50E	920	410
7.50-16	10PR	TT/TL	788	211	5.50F	1215	410
9.00-16	10PR	TT/TL	845	234	6LB	1500	360
10.5/80-18	12PR	TT/TL	885	276	9.0	1950	410
26X12.00-12	12PR	TL	648	307	10.50L	810	140

## JT-AG209



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
600-16	8PR	TT	740	160	4.50E	580	360
650-16	8PR	TT	760	170	4.50E	630	340
750-16	8PR	TT	810	205	5.50F	870	370
900-16	8PR	TT	860	235	6LB	1060	300



## JT-F2

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
4.00-12	6PR	TT/TL	535	110	4.00E	250	340
4.00-14	6PR	TT/TL	590	110	3.00D	400	340
4.00-15	6PR	TT/TL	610	110	3.00D	290	340
4.00-16	6PR	TT/TL	640	110	3.00D	420	340
4.00-19	6PR	TT/TL	712	112	3.00D	345	340
4.50-16	6PR	TT/TL	655	122	3.00D	360	360
5.00-15	6PR	TT/TL	665	140	4J	365	280
5.00-16	6PR	TT/TL	660	140	4.00E	450	280
5.50-16	6PR	TT/TL	710	150	4.00E	530	370
6.00-14	8PR	TT/TL	690	165	4.50E	450	250
6.00-16	8PR	TT/TL	740	160	4.00E	590	360
6.50-16	8PR	TT/TL	760	170	4.50E	630	340
6.50-20	8PR	TT/TL	880	180	5.50F	865	420
7.5L-15	8PR	TL	745	208	6LB	840	370
7.50-16	8PR	TT/TL	810	205	5.50F	870	370
7.50-18	8PR	TT/TL	855	205	5.50F	945	370
7.50-20	10PR	TT/TL	928	215	5.50F	780	210
9.00-16	10PR	TT/TL	845	234	8.50H	1200	400
10.00-15	10PR	TT	855	278	8LB	1425	240
10.00-16	10PR	TT/TL	895	274	W8L	1325	340
11.00-16	10PR	TT/TL	965	315	W10L	1485	310

## JT-F2 4RIB

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
26x12.00-12	6PR	TT/TL	660	305	10.50I	810	140
9.00-16	10PR	TT/TL	845	234	8.50H	1200	400
10.00-16	10PR	TT/TL	894	274	W8L	1280	390
11.00-16	10PR	TT/TL	965	315	W10L	1350	345



## PADDY TIRE

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
650-16	6PR	TT	830	165	5.00F	565	250
750-16	8PR	TT	895	200	5.50F	775	320
8.3-20	6PR	TT	950	210	W7	970	270
8.3-24	6PR	TT	1050	210	W7	1135	270
9.5-20	8PR	TT	1050	240	W8	1245	280
9.5-24	6PR	TT	1150	240	W8	1150	240
11.2-24	6PR	TT	1205	285	W10	1485	210
12.4-28	6PR	TT	1315	315	W11	1785	200
11-32	6PR	TT	1490	305	W10	1080	160



## IRRIGATION TIRE

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
11.2-24	8PR	TT	1105	285	W10	1045	180
11.2-38	8PR	TT	1459	285	W10	1150	180
13.6-24	8PR	TT	1210	345	W12	1545	210
14.9-24	8PR	TT	1265	378	W12	1850	180
16.9-28	8PR	TT	1435	430	W15L	2575	240





## JT-IM-F600A

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10.0/75-15.3	10PR	TL	760	264	9.00	1550	390
10.0/75-15.3	12PR	TL	760	264	9.00	1700	470
10.5/80-18	12PR	TL	907	274	9.00	2120	410
11.5/80-15.3	12PR	TL	845	290	9.00	2180	410
11.5/80-15.3	14PR	TL	845	290	9.00	2430	475
12.5/80-15.3	14PR	TL	889	307	10.00	2650	430
12.5/80-15.3	16PR	TL	889	307	10.00	2820	490
12.5/80-18	12PR	TL	965	308	9.00	2650	370
12.5/80-18	14PR	TL	965	308	9.00	3000	430
13.0/85-18	14PR	TL	890	336	11.00	2575	430
13.0/85-18	16PR	TL	890	336	11.00	2800	490



## JT-IM-F600B

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10.0/80-12	10PR	TL	710	264	9.00	1295	390
10.5/85-16	14PR	TL	755	274	9.00	1900	530



## JT-IM-M600

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10.0/75-15.3	12PR	TL	760	264	9.00	1700	470
10.0/75-15.3	14PR	TL	760	264	9.00	1900	550
11.5/80-15.3	12PR	TL	845	290	9.00	2180	410
11.5/80-15.3	14PR	TL	845	290	9.00	2430	475

## JT-IM-M700



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
405/70-20	14PR	TL	1076	405	13.00	3250	350
405/70-24	14PR	TL	1178	405	13.00	3550	350

## JT-IM-M800



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
15.5/80-24	14PR	TL	1262	394	13.00	2900	300
405/70-20	14PR	TL	1076	405	13.00	3250	350
405/70-24	14PR	TL	1178	405	13.00	3550	350
10.0/75-15.3	12PR	TL	760	264	9.00	1700	470
11.5/80-15.3	12PR	TL	845	290	9.00	2180	410

## JT-IM-M900



SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
26X12-12	4PR	TL	660	305	10.50I	810	140
26X12-12	6PR	TL	660	305	10.50I	810	140
31X15.5-15	8PR	TL	787	381	13.00	810	140
29X12.5-15	6PR	TL	750	310	10.00	690	210



## JT-IM-M1000

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
28L-26	18PR	TT/TL	1645	715	DW25A	4800	210
30.5L-32	18PR	TT/TL	1845	775	DH27	5950	210



## JT-AG 200

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
16.5/70-18	14PR	TL	1065	425	W13	3200	370
15.5/65-18	10PR	TL	980	395	W13	2275	350



## JT-AG 202

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
15.5/65-18	10PR	TL	915	395	W13	2300	350
18.0-15.5	10PR	TL	980	450	13.00	4185	350



## JT-M 102

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
600-16	8PR	TT	745	165	4.50E	750	420
600-16	10PR	TT	745	165	4.50E	800	430
650-16	8PR	TT	765	180	5.50F	850	420
650-16	10PR	TT	765	180	5.50F	890	430
700-16	10PR	TT	775	200	5.50F	1220	630

## JT-FL 500A

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
26 x 12-12	6PR	TL	660	305	10.50I	810	140
500/45-22.5	16PR	TL	1020	500	16.00	3350	280
550/45-22.5	16PR	TL	1070	550	16.00	4375	280
500/60-22.5	16PR	TL	1172	500	16.00	4875	320
600/50-22.5	16PR	TL	1170	600	20.00	4375	200
600/55-22.5	16PR	TL	1238	600	20.00	4375	280
600/55-26.5	16PR	TL	1333	600	20.00	5800	260



## JT-FL 500B

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
400/60-15.5	16PR	TL	874	400	13.00	2900	250
400/55-22.5	16PR	TL	1020	400	11.75	3650	350
700/50-26.5	16PR	TL	1333	700	24.00	5800	180
700/55-26.5	16PR	TL	1440	700	24.00	5800	180



一流的产品, 永久的服务, 创造价值, 回报社会

FIRST-CLASS PRODUCTS, PERMANENT SERVICE, CREATE VALUE, RETURN SOCIETY



## TRAILER TIRE

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
10.00-20	14PR	TT	1055	278	7.50	2430	620
11.00-22.5	16PR	TL	1055	293	8.25	3000	810



## MOBILE HOME TIRE

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
8-14.5	12PR	TL	707	203	6.00MH	1380	690



## ST TRAILER TIRE

SIZE	PLY RATING	TYPE	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
ST 175/80D13	6PR	TL	626	184	5J	670	350
ST 206/75D14	6PR	TL	664	203	5.5J	800	350
ST 206/75D15	6PR	TL	689	203	5.5J	825	350
ST 225/75D15	8PR	TL	719	223	6J	1150	450



## JT-LUG

SIZE	PLY RATING	TYPE	PATTERN	OVERALL DIAMETER mm	SECTION WIDTH mm	STANDARD RIM	LOAD CAPACITY/ KG	INFLATION PRESSURE / KPA
500-12	8PR	TT	RIB / LUG	568	143	3.00B	485	400
550-13	8PR	TT	RIB / LUG	620	160	4J	565	420
560-13	6PR	TT	RIB / LUG	625	145	4J	475	170
600-14	8PR	TT	RIB / LUG	680	170	4 1/2J	685	420
600-16	10PR	TT	RIB / LUG	730	170	4.50 E	860	530
650-14	8PR	TT	RIB / LUG	705	180	4 1/2J	785	420
650-15	8PR	TT	RIB / LUG	730	180	4.50 E	830	420
650-16	10PR	TT	RIB / LUG	750	185	5.50F	975	530
700-15	10PR	TT	RIB / LUG	750	200	5.50F	1040	530
700-16	12PR	TT	RIB / LUG	775	200	5.50F	1220	630
700-20	12PR	TT	RIB / LUG	904	200	5.5	1580	740
750-15	12PR	TT	RIB / LUG	780	215	6.00 G	1370	630
750-16	12PR	TT	RIB / LUG	805	215	6.00 G	1405	630
750-20	14PR	TT	RIB / LUG	935	215	6.0	1885	810
825-16	14PR	TT	RIB / LUG	855	235	6.50H	1705	630
825-20	14PR	TT	RIB / LUG	974	235	6.5	2205	810
900-20	14PR	TT	RIB / LUG	1018	259	7.0	2575	770
1000-20	16PR	TT	RIB / LUG	1055	278	7.5	3000	810
1100-20	16PR	TT	RIB / LUG	1085	293	8.0	3270	810
1100-22	16PR	TT	RIB / LUG	1135	293	8.0	3480	810
1200-20	18PR	TT	RIB / LUG	1125	315	8.5	3730	810
1200-24	18PR	TT	RIB / LUG	1225	315	8.5	4195	810



## JT-RIB