

Infinity

BALTYRE



LR451



LR650



LR700



LR861

Dezén	Rozmer	TT/TL	LI/SI	LI	SI	Ráfik	Hĺbka dezénu (mm)	Hmotnosť	Maximálna záťaž (kg)	Celkový priemer (mm)	Šírka prierezu (mm)	Hustenie (kPa)
LR451	LI 500/70R24	TL	164A8/164B	164A8	164B	DW16L	35,0	107,40	5000	1310	503	400
LR650	LI 540/65R24	TL	140D/143A8	140D	43A8	W16L	48,0	110,59	2500	1312	550	160
	LI 540/65R28	TL	142D/145A8	142D	45A8	W16L	48,0	123,17	2650	1413	550	160
	LI 540/65R30	TL	150D/153A8	150D	53A8	W16L	48,0	128,55	3350	1464	550	240
	LI 540/65R34	TL	145D/148A8	145D	48A8	W16L	48,0	140,67	2900	1566	550	160
	LI 600/65R28	TL	147D/150A8	147D	50A8	DW20B	52,0	148,81	3075	1491	591	160
	LI 600/65R38	TL	153D/156A8	153D	56A8	DW20B	52,0	185,20	3650	1745	591	160
	LI 650/65R38	TL	157D/160A8	157D	60A8	DW20B	56,0	221,26	4125	1811	645	160
	LI 650/65R42	TL	165D/168A8	165D	68A8	DW20B	56,0	239,12	5150	1913	645	240
	LI 710/70R38	TL	169A8/166D	169A8	166D	DW23B	57,0	291,90	5300	1959	716	160
	LI 710/70R42	TL	171A8/168D	171A8	168D	DW23B	57,0	313,40	5600	2061	716	160
LR700	LI 360/70R24	TL	127A8/124B	127A8	124B	W11	42,0	63,10	1750	1152	357	240
	LI 480/70R28	TL	140A8/137B	140A8	137B	W15L	47,0	106,60	2500	1421	479	160
	LI 480/70R34	TL	143A8/143B	143A8	143B	W15L	47,0	130,70	2725	1580	479	160
	LI 480/70R38	TL	145A8/142B	145A8	142B	W15L	47,0	136,10	2900	1681	479	160
	LI 520/70R38	TL	150A8/150B	150A8	150B	W16L	48,0	159,85	3350	1749	516	160
	LI 580/70R38	TL	155A8/155B	155A8	155B	W18L	50,0	190,54	3875	1827	577	160
	LI 600/70R30	TL	152D	152D	152D	DW20B	52,5	170,70	3550	1602	591	160
LR861	LI 280/85R24	TL	115A8/112B	115A8	112B	W10	39,0	45,60	1215	1086	282	160
	LI 320/85R24	TL	122A8/119B	122A8	119B	W11	41,0	55,60	1500	1154	319	160
	LI 340/85R24	TL	125A8/122B	125A8	122B	W12	42,0	59,30	1650	1188	343	160
	LI 340/85R28	TL	127A8/124B	127A8	124B	W12	42,0	65,50	1750	1289	343	160
	LI 380/85R28	TL	133A8/130B	133A8	130B	W12	45,0	82,30	2060	1357	380	160
	LI 420/85R24	TL	137A8/134B	137A8	134B	W15L	48,0	88,40	2300	1324	418	160
	LI 420/85R28	TL	139A8/136B	139A8	136B	W15L	48,0	97,80	2430	1425	418	160
	LI 420/85R30	TL	140A8/137B	140A8	137B	W15L	48,0	101,80	2500	1476	418	160
	LI 460/85R34	TL	147A8/144B	147A8	144B	W16L	51,0	125,30	3075	1646	455	160
	LI 460/85R38	TL	149A8/146B	149A8	146B	W16L	51,0	136,10	3250	1747	455	160
	LI 520/85R38	TL	155A8/152B	155A8	152B	DW16L	54,0	179,10	3875	1849	516	160