



AGRO PNEUMATIKY



F-35



VL-40



JAF-318



F-2AD



F-2A



VL-29



VL-28



VL-31



VL-32



DR-108



VL-41



VL-44



DR-106



DR-109



DT-112



DF-101



V-103



DT-113



V-105A



DF-1



DR-103



JA-183



TVL-2



IR-110



IR-107

INDUSTRIÁLNE PNEUMATIKY



F-201



VF-76B



VL-30



DT-114



DT-122

AGRO PNEUMATIKY

DEZÉN	ROZMER	LI/SI	MAXIMÁLNA RÝCHLOSŤ (km/h)	MAXIMÁLNE ZAŤAŽENIE (kg)	HUSTENIE (kpa)	CELKOVÝ PRIEMER (mm)	CELKOVÁ ŠÍRKA (mm)	VEĽKOSŤ DISKU	PR	VÁHA	TL/TT
F-35	11,2-20	114A6	30	1180	210	985 ⁺¹⁵ ₋₂₀	284	W10/W9,W7	8	48	TT
VL-40	11,2-20	120A8	40	1400	240	1005 ⁺³⁵ ₋₂₀	284	W10/W9,W7	8	35	TT
Jaf-318	13,6R38	128A6	30	1800	160	1550 ⁺²³ ₋₂₄	345	W12,DW12/W11,DW11	6	87	TT
F-2AD	15,5-38	133A6	30	2060	180	1570 ⁺⁴² ₋₂₄	394	DW14L,W14L/DW11	8	103	TT
F-2A	15,5R38	134A8	40	2120	160	1565 ±24	394	W14L/DW14L	8	110	TT
VL-29	16,9R30	155A8	40	3875	360	1475 ±29	429	W15L/DW14	14	137	TT
VL-28	16,9R38	141A8	40	2575	160	1675 ±28	429	DW16/DW15	8	150	TT
VL-31	18,4R34	157A8	40	4125	300	1645 ±31	467	DW16/DW15	14	170	TT
VL-31	18,4R34	144A8	40	2800	160	1645 ±31	467	DW16/DW15	8	155	TT
VL-32	18,4R38	165A8	40	5150	310	1750 ±31	467	W16L/DW16,W15L	16	168	TT
DR-108	21,3R24	140A6	30	2500	160	1400 ±32	540	DW18	-	150	TT
VL-41	28,1R26	158A8	40	4250	160	1722 ±42	728	DW25/DW24	12	235	TT
VL-44	360/70R20	120A8	40	1400	160	1042 ±21	357	W11/W10,W12	-	61	TT
VL-44	360/70R24	122A8	40	1500	160	1152 ±22	357	W11/W10,W12	-	67	TT
DR-106	420/70R24	130A8	40	1900	160	1245 ±19	418	W13/w12,DW12,DW13,W14L,DW14L	-	89	TL
DR-109	420/85R28	139A8	40	2430	160	1428 ±29	438	W15L/DW15L,W14L,DW14L	-	125	TL
VL-44	480/70R34	143A8	40	2725	160	1580 ±24	480	W15L/W14L,W16L,DW14L,DW16L	-	134	TT
DT-112	600/55-26,5	170A6	30	6000	260	1333 ⁺⁴⁷ ₋₂₆	600	20,00x26,5	16	180	TT
DF-101	650/75R32	172A8	40	6300	320	1789 ±39	655	DW21A-32/DW20A-32	-	280	TL
V-103	7,50-20	103A6	30	875	280	915 ⁺²⁸ ₋₁₇	205	5,50F/5,00F	6	28	TT
DT-113	700/50-26,5	163A8	40	4875	400	1373 ⁺⁴⁹ ₋₂₈	700	AG24,00-26,5	16	200	TT
V-105A	8,3-20	106A6	30	850	250	912 ⁺²⁸ ₋₁₆	211	W7	8	38	TT
DF-1	800/65R32	172A8	40	6300	240	1853 ±42	818	DW27/DW25	-	330	TL
DR-103	800/65R32	172A8	40	6300	240	1853 ±42	818	DW27A-32/DW25B-32,DH27B-32	-	335	TL
DR-103	800/65R32	172A8	40	6300	240	1853 ±42	818	DW27A-32/DW25B-32,DH27B-32	-	352	TT
Ja-183	9,5-42	116A6	30	1250	210	1505 ⁺³¹ ₋₁₈	241	W8,DW8	6	62	TT
TVL-2	10,0/75-15,3	126A6	30	1695	470	760 ⁺²⁶ ₋₁₅	264	9,00-15,3	12	30	TT
TVL-2	10,0/75-15,3	130A6	30	1900	550	760 ⁺²⁶ ₋₁₅	264	9,00-15,3	14	32	TT
IR-110	12,00-16	126A6	30	1700	250	924 ⁺³⁶ ₋₂₁	305	W8	8	36	TT
IR-107	9,00-16	121A8	40	1450	335	855 ⁺¹⁹ ₋₁₁	234	6,00F	10	25,7	TT

INDUSTRIÁLNE PNEUMATIKY

DEZÉN	ROZMER	LI/SI	MAXIMÁLNA RÝCHLOSŤ (km/h)	MAXIMÁLNE ZAŤAŽENIE (kg)	HUSTENIE (kpa)	CELKOVÝ PRIEMER (mm)	CELKOVÁ ŠÍRKA (mm)	VEĽKOSŤ DISKU	PR	VÁHA	TL/TT
F-201	10,0/75-15,3	130A6	30	1900	550	785 ±12	267	9,00-15,3	14	40	TT
F-201	10,0/75-15,3	126A6	30	1695	470	785 ±12	267	9,00-15,3	12	30	TT
F-201	10,0/75-15,3	123A6	30	1525	390	785 ±12	267	9,00-15,3	10	30	TT
VF-76B	18,00-25	183B	50	8750	575±25	1615 ±25	498±15	13	32	350	TT
VL-30	10,0/75-15,3	126A6	30	1695	470	780 ⁺²⁷ ₋₁₆	264	9,00-15,3	12	38	TT
VL-30	10,0/75-15,3	123A6	30	1525	390	780 ⁺²⁷ ₋₁₆	264	9,00-15,3	10	38	TT
DT-114	10,00-20	146A8	40	3000	750	1075 ±16	278	7,50-20/7,0-20/8,0-20	16	57	TT
DT-122	10-16,5	130A2	10	1900	410	777	262	8,25-16,5	8	25	TL
DT-122	12-16,5	140A2	10	2500	458	831	325	9,75-16,5	10	35	TL



OFFROAD PNEUMATIKY

DEZÉN	ROZMER	LI/SI	MAXIMÁLNA RÝCHLOSŤ (km/h)	MAXIMÁLNE ZAŤAŽENIE (kg)	HUSTENIE (kpa)	CELKOVÝ PRIEMER (mm)	CELKOVÁ ŠÍRKA (mm)	VEĽKOSŤ DISKU	PR	VÁHA	TL/TT
VLI-5	6,95-16(175/80-16)	85P	150	515	210	692 ±7	178	5J	6	12,6	TT

F-201